

## AGRIMAX TURF RT 333 - Data Sheet



### Description

AGRIMAX TURF RT 333 (R-3+) is a radial tire designed for small tractors in gardening, vineyards and orchards applications. Its rounded shoulder design provides low soil compaction and makes it extremely delicate on the ground. Its unique extra-deep tread (R-3+) and the special design with directional blocks stand for excellent traction both in the field and on the road, and an extended tire life cycle. AGRIMAX TURF RT 333 (R-3+) ensures great self-cleaning properties and thanks to its low rolling resistance, allows for significant fuel saving.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agriculture: Orchard Harvester • Small Tractor • Vineyard Harvester

SIZE	Version	USACode	TRA Code	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
<b>220/55 R12</b>	STANDARD	94070237		82 A8/B	W7		8.7	21.7	9.8	64.8	TL	E11-106R-007600
<b>240/60 R12</b>	STANDARD	94070657		89 A8/B	W7		9.5	23.3	10.6	70	TL	E11-106R-007679
<b>200/65 R16</b>	STANDARD	94070640		94 A8/B	W6		8	26.2	12.2	78.7	TL	E11-106R-007678
<b>200/70 R 16</b>	STANDARD	94074136	R1W	94 A8/B	W 6		7.9	27	12.5	80.9	TL	E11-106R-008659
<b>240/70 R16</b>	STANDARD	94070282		104 A8/B	W8	W 8 L ; W 9	9.6	29.2	13.4	87.1	TL	E11-106R-007531
<b>260/70 R 16</b>	STANDARD	94067909		109 A8/109 B	W 8	W 8 L ; W 9	10.2	30.3	13.7	90	TL	E11-106R-007158
<b>280/70 R 16</b>	STANDARD	94065714		112 A8/112 B	W9	W 8 ; W 10	11.4	31.5	14.1	93.3	TL	E11-106R-006472
<b>280/70 R 18</b>	STANDARD	94065707		114 A8/114 B	W 9	W 8 ; W 10	11.4	33.1	15.4	100.4	TL	E11-106R-006473
<b>320/65 R 18</b>	STANDARD	94071081		109 A8/109 B	W 10	W 9 ; W 11	12.6	34.4	15.5	102	TL	E11-106R-007844
<b>300/70 R 20</b>	STANDARD	9406748		110 A8/110 B	W9	W10	11.6	37.5	17	111.3	TL	E11-106R-006943
<b>320/70 R 20</b>	STANDARD	94067558		113 A8/113 B	W10	W9 ; W11	12.6	38.7	17.4	114.8	TL	E11-106R-006944
<b>380/70 R 20</b>	STANDARD	94068821		122 A8/122 B	W 12	W 11 ; W 13	15	42.6	19.1	126.5	TL	E11-106R-007111
<b>360/70 R 24</b>	STANDARD	94067916		122 A8/122 B	W 11	W 10 ; W 12	14.1	45.4	20.4	134.2	TL	E11-106R-007110
<b>380/70 R 24</b>	STANDARD	94068838		125 A8/125 B	W 12	W 11 ; W 13	15	46.9	21	139.3	TL	E11-106R-007112
<b>420/70 R 24</b>	STANDARD	94069460		130 A8 / 130 B	W 13	W 12 ; W 14 L	16.5	49.1	21.9	146.8	TL	E11-106R-007206
<b>480/70 R 28</b>	STANDARD	94075393		140 A8 / 140 B	W 15 L	W 14 L ; W 16 L	18.9	55.9	24.8	166.5	TL	E11-106R-009049
<b>480/70 R 30</b>	STANDARD	94075409		141 A8 / 141 B	W 15 L	W 14 L ; W 16 L	18.9	58.2	26	173.1	TL	E11-106R-009050
<b>480/70 R 34</b>	STANDARD	94075232		149 A8 / 149 B	W 15 L	W 14 L ; W 16 L	18.9	62.2	28.5	188.4	TL	E11-106R-009042

Printed on 5/18/2024 9:38 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..