

RIDEMAX FL 693 M - Technical Specifications



Description

RIDEMAX FL 693 M is the ideal radial tire for those who frequently travel on the road with trailers/tank trucks. Actually designed for 75% on-the-road use, RIDEMAX FL 693 M provides excellent road performance prioritizing both comfort and self-cleaning properties. The speed index classes D/E of the range stands for higher speeds when travelling on the road leading to significant time savings. The low rolling resistance contributes to less fuel consumption, while a reinforced bead and steel belts ensure enhanced durability.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Tanker • Trailer

Version	STANDARD
Type	TL
Tyre Size	500/50 R 17
LI/SS	149 D/146 E

Dimensions International Standard

Section Width (mm)	503
Overall Diameter (mm)	932
Static Loaded Radius (mm)	424
Rolling Circumference (mm)	2913
SRI (mm)	450
Rim Rec	16.00
ECE	E4-106R-001821

Load capacity (Kg)

km/h / bar	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	5.0
70	990	1110	1350	1530	1770	2010	2220	2430	2670	3000
65	1075	1205	1465	1660	1920	2180	2405	2635	2895	3250
50	1305	1460	1775	2010	2325	2640	2915	3190	3505	3935
40	1465	1640	1990	2255	2610	2965	3275	3585	3935	4420
25	1695	1900	2315	2620	3030	3445	3800	4160	4575	5135
10	1935	2165	2635	2985	3455	3920	4330	4740	5210	5850

Printed on 5/19/2024 4:21 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..