

# RIDEMAX FL 693 M - Technical Specifications



## Description

RIDEMAX FL 693 M is the ideal radial tire for those who frequently travel on the road with trailers/tank trucks. Actually designed for 75% on-the-road use, RIDEMAX FL 693 M provides excellent road performance prioritizing both comfort and self-cleaning properties. The speed index classes D/E of the range stands for higher speeds when travelling on the road leading to significant time savings. The low rolling resistance contributes to less fuel consumption, while a reinforced bead and steel belts ensure enhanced durability.

## UM

US Standard

## Construction

 RADIAL

## Machinery

Agriculture: Tanker • Trailer

Version	HD
Type	TL
Tyre Size	600/55 R 26.5
LI/SS	177 D

## Dimensions US Standard

Usa code	94049615
Section Width (inch)	24.1
Overall Diameter (inch)	52.5
Static Loaded Radius (inch)	23.1
Rolling Circumference (inch)	160.5
Rim Rec	AG 20.00
ECE	E11-106R-003007

## Load capacity (lbs)

mph / psi	15	17	23	29	35	41	46	52	58	73	87
45	4990	5960	7240	8380	9660	10950	11750	13040	14330	15130	16090
40	6040	7210	8770	10130	11690	13250	14220	15780	17340	18310	19480
30	6790	8100	9850	11390	13140	14890	15980	17740	19490	20580	21890
25	7540	8990	10950	12640	14580	16530	17750	19700	21640	22850	24300
15	7890	9410	11450	13230	15270	17290	18570	20600	22640	23910	25430
5	8980	10720	13040	15070	17380	19710	21150	23470	25780	27240	28970

Printed on 5/19/2024 2:07 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..