

RIDEMAX IT 697 (M+S) - Data Sheet



Description

RIDEMAX IT 697 M+S represents the best response to the needs of modern farming contractors during winter operations. It is perfect for haulage and municipality applications. This winter tire for tractors ensures extraordinary grip for all operations on icy and snowy roads without the need of snow chains being mounted. Thanks to the tread grooves and the strong casing, a tractor can be driven in full stability, also at high speed levels. The tread design has been specially developed for heavy-duty services and ensures a low rolling resistance that provides fuel economy plus great stability.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Tractor

SIZE	Version	USACode	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	TMPH	ECE
460/70 R 24 IND	STANDARD	94067039	157A8/152D	DW 15 L	DW14 L; DW 16L	18.3	49.4	22.5	148.5	TL	0	E11-106R-006840
540/70R24 IND	STANDARD	94072910	170D/175A8	DW 16 L	DW18 L	21.1	53.9	24.6	164.6	TL	0	E11-106R-007933
480/65 R 28 IND	STANDARD	94062720	149 D/154 A8	DW 15 L	DW 14 L ; DW 16 L	18.9	52.6	24.2	160.9	TL	0	E11-106R-006159
540/65 R28 IND	STANDARD	94055401	155 D/160 A8	W 16 L	W 18	20.9	55.6	25.3	168.3	TL	0	E11-106R-004076
600/65 R 28 IND	STANDARD	94066995	165 A8/160 D	W 18 L	DW 20 B	23.3	58.7	26.9	177.5	TL	0	E11-106R-006760
540/65 R 30 IND	STANDARD	94048106	156 D/161 A8	W 16 L	W 18	20.9	57.6	26.5	175	TL	0	E11-106R-003015
600/70 R 30 IND	STANDARD	94058037	166 D/171 A8	DW 18 L	DW 20 B	23.6	63	27.1	189.8	TL	1	E11-106R-005177
600/65 R 38 IND	STANDARD	94062812	166 D/170 A8	DW 18 L	DW 20 B	23.2	68.7	31.3	209.3	TL	0	E11-106R-005855
650/65 R 38 IND	STANDARD	94055418	170 D/175 A8	DW 20 B	DW 18 L	25.4	71.3	32.4	217.1	TL	1	E11-106R-004078
650/85 R 38 IND	STANDARD	94066322	178 D/ 183 A8	DW 23 B	DW 20 B ; DW 21 B	27.9	81.5	38.3	247.2	TL	0	E11-106R-006761
710/70 R 38 IND	STANDARD	94067084	177D / 182A8	DW 23 B	DW 25 B	28.2	77.1	35.4	234.3	TL	0	E11-106R-006762
650/65 R 42 IND	STANDARD	94050109	171 D/176 A8	DW 20 B	DW 18 L	25.4	75.6	34.6	231.1	TL	0	E4-106R-002659
710/70 R 42 IND	STANDARD	94058099	180 D/185 A8	DW23 B		28.2	81.4	36.5	246.6	TL	1	'E11-106R-005178

Printed on 5/18/2024 10:24 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..