



TR 463 - Data Sheet

Description

TR 463 has been specially designed for backhoe loaders and industrial tractors. Made of a superior tread compound and featuring a strong nylon casing, this tire stands for best results in industrial and OTR applications, and on construction sites. TR 463 provides excellent traction for drive wheels.



UM

International Standard

Construction

 BIAS

Machinery

Industrial: Backhoe Loader • Industrial Tractor

| SIZE | Version | TRA Code | LI/SS | PR | RIM REC | RIM ALT | SW | OD | SLR | RC | SRI | Type | ECE |
|-----------|------------|----------|--------|----|---------|---------|-----|------|-----|------|-----|------|-----------------|
| 16.9 - 24 | INDUSTRIAL | R4 | 149 A8 | 12 | DW 15 L | DW 14 L | 445 | 1300 | 584 | 3877 | | TL | |
| 18.4 - 26 | INDUSTRIAL | R4 | 156 A8 | 12 | DW 16 L | DW 15 L | 480 | 1425 | 637 | 4215 | 675 | TL | |
| 16.9 - 28 | INDUSTRIAL | R4 | 152 A8 | 12 | DW 15 L | DW 14 L | 450 | 1405 | 636 | 4190 | | TL | E11-106R-003626 |

Printed on 5/19/2024 1:13 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..