

## AT 621 - Technische Daten



### Description

AT 621 eignet sich für Baggerlader und Kompaktlader bei allen Bagger- und Ladearbeiten in der Landwirtschaft. Der AT 621 Reifen zeichnet sich durch eine extra tiefe Lauffläche aus, welche ausgezeichnete Schnitt- und Rissfestigkeit sowie höhere Beständigkeit bietet. Außerdem zeichnet sich dieser BKT Reifen durch hervorragende Selbstreinigungseigenschaften aus. AT 621 ist in verschiedenen Ausführungen erhältlich, um den unterschiedlichsten Nutzeranforderungen gerecht zu werden.

### UM

US Standard

### Construction

 BIAS

### Machinery

Landwirtschaft: Kompaktlader • Baggerlader  
Industrie: Baggerlader • Radlader

Version	STANDARD
Type	TT
Tyre Size	12.5/80 - 18
LI/SS DRIVE WHEEL	135 A8
LI/SS FREE ROLLING	148 A8

## Dimensions US Standard

Usa code	94019748
Ply Rating	16
Section Width (inch)	12.1
Overall Diameter (inch)	38.9
Static Loaded Radius (inch)	17.1
Rolling Circumference (inch)	114.8
Rim Rec	W 9
Rim Alt	11.0
ECE	E11-106R-006957
TRA Code	R4

## Load capacity (lbs)

mph / psi	71
5 FR	9720
15 FR	8270
20 FR	7780
25 FR	6940
5 DW	6720
15 DW	5720
20 DW	5380
25 DW	4810

Printed on 19.05.2024 11:10

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..