

## EARTHMAX SR 484 - Datenblatt



### Description

Der EARTHMAX SR 484 ist ein Vollstahl-Radialreifen, der speziell für starre Muldenkipper für den Transport im Tagebau entwickelt wurde. Er verfügt über ein einzigartiges E-3-Laufflächendesign mit einer speziellen Laufflächenmischung, die einen hervorragenden Schutz bei rauen und felsigen Bedingungen sowie eine verbesserte Traktion und hervorragende Selbstreinigungseigenschaften gewährleistet. Die Vollstahlkonstruktion mit mehrlagigen Stahlgürteln bietet einen hervorragenden Schutz gegen Stöße, Ermüdung und Durchschläge aufgrund von Gestein und erhöht die Betriebszeit und Produktivität. Der EARTHMAX SR 484 verfügt über ein quadratisches Schulterdesign, das den Bodenkontakt maximiert und eine hervorragende Manövrierfähigkeit und Stabilität gewährleistet. Dieser BKT-Reifen ist speziell für höhere Geschwindigkeiten und lange Strecken konzipiert.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Starrer Muldenkipper

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TMPH
27.00 R 49	CUT RESISTANT COMPOUND	94067817	E3	**	223 B	19.50/4.0	--	28.9	104.2	47	317.1	TL	360
27.00 R 49	HEAT RESISTANT COMPOUND	94067824	E3	**	223 B	19.50/4.0	--	28.9	104.2	47	317.1	TL	486
27.00 R 49	STANDARD COMPOUND	94067831	E3	**	223 B	19.50/4.0	--	28.9	104.2	47	317.1	TL	418

Printed on 19.05.2024 17:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..