

TR 463 - Technische Daten



Description

TR 463 wurde speziell für Baggerlader und Industrieschlepper entworfen. Hergestellt aus einer erstklassigen Gummimischung und mit einer robusten Nylonkarkasse, steht dieser Reifen für beste Ergebnisse in industriellen und OTR-Anwendungen sowie auf Baustellen. TR 463 verleiht den Antriebsrädern hervorragende Traktion.

UM

US Standard

Construction

 BIAS

Machinery

Industrie: Baggerlader • Traktor

Version	INDUSTRIAL
Type	TL
Tyre Size	16.9 - 24
LI/SS	149 A8

Dimensions US Standard

Usa code	94053322
Ply Rating	12
Section Width (inch)	17.5
Overall Diameter (inch)	51.2
Static Loaded Radius (inch)	23
Rolling Circumference (inch)	152.6
Rim Rec	DW 15 L
Rim Alt	DW 14 L
TRA Code	R4

Load capacity (lbs)

mph / psi	38
25	7150

Printed on 18.05.2024 17:53

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..