

XL GRIP (BHL) - Technische Daten



Description

XL GRIP (BHL) wurde speziell für Baggerlader entwickelt, die Schwersteinsatz in den Anwendungen Graben, Planieren und Laden leisten. Das nicht richtungsgebundene Muster der Lauffläche sichert beste Traktion und Stabilität. Die spezielle Laufflächenmischung zeigt sich in hervorragender Schnitt- und Durchstoßfestigkeit und verlängert die Lebensdauer der Lauffläche.

UM

US Standard

Construction

 BIAS

Machinery

Industrie: Baggerlader

Version	ARAMID + STEEL BELTED
Type	TT
Tyre Size	10.00 - 20

Dimensions US Standard

Usa code	94050727
Ply Rating	18
Overall Width (inch)	11.2
Overall Diameter (inch)	42.3
Static Loaded Radius (inch)	19.9
Rolling Circumference (inch)	128.2
Rim Rec	7.5
Rim Alt	7.0

Load capacity (lbs)

mph / psi	120	110
5	9880	-
25	-	7290

Printed on 18.05.2024 18:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..