

AGRIMAX RT 600 - Especificaciones técnicas

Description

AGRIMAX RT 600 es el neumático ideal para utilizarlo en cubiertas herbáceas y actividades de cosecha y pulverización. Gracias a su amplia área de contacto, AGRIMAX RT 600 garantiza una óptima distribución de la presión sobre el terreno reduciendo los daños de prados y protege el suelo. Gracias a la tecnología con hombro redundado, la banda de rodamiento reforzada y el número mayor de tacos, el neumático asegura una grande estabilidad y excelente tracción.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Cosechadora • Esparcidor • Tractor



Version	STANDARD
Type	TL
Tyre Size	540/65 R 28
LI/SS	142 D/145 A8

Dimensions International Standard

Section Width (mm)	530
Overall Diameter (mm)	1413
Static Loaded Radius (mm)	642
Rolling Circumference (mm)	4202
SRI (mm)	675
Rim Rec	W 16 L
Rim Alt	W 18 L
ECE	E11-106R-002980

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
65	1485	1750	1990	2230	2440	2650
50	1560	1840	2090	2340	2565	2785
40	1625	1915	2175	2440	2670	2900
30	1710	2015	2290	2565	2810	3050
10 LT	1995	2350	2670	2990	3275	3555
10 HT	1710	2015	2290	2565	2810	3050

Printed on 18/05/2024 19:58

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..