

## AGRIMAX RT 600 - Especificaciones técnicas

### Description

AGRIMAX RT 600 es el neumático ideal para utilizarlo en cubiertas herbáceas y actividades de cosecha y pulverización. Gracias a su amplia área de contacto, AGRIMAX RT 600 garantiza una óptima distribución de la presión sobre el terreno reduciendo los daños de prados y protege el suelo. Gracias a la tecnología con hombro redundado, la banda de rodamiento reforzada y el número mayor de tacos, el neumático asegura una grande estabilidad y excelente tracción.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agricultura: Cosechadora • Esparcidor • Tractor



|           |             |
|-----------|-------------|
| Version   | STANDARD    |
| Type      | TL          |
| Tyre Size | 750/65 R 26 |
| LI/SS     | 171 A8/B    |

## Dimensions International Standard

|                            |                   |
|----------------------------|-------------------|
| Section Width (mm)         | 750               |
| Overall Diameter (mm)      | 1636              |
| Static Loaded Radius (mm)  | 737               |
| Rolling Circumference (mm) | 4987              |
| SRI (mm)                   | 775               |
| Rim Rec                    | DW 24 B           |
| Rim Alt                    | DW 23 B ; DW 25 B |
| ECE                        | E11-106R-006182   |

## Load capacity (Kg)

| km/h / bar | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  | 2.0  | 2.4  | 2.8  | 3.2  | 3.4   | 3.8   |
|------------|------|------|------|------|------|------|------|------|------|-------|-------|
| 50         | 2830 | 3260 | 3690 | 4000 | 4370 | 4860 | 5230 | 5720 | 6150 | -     | -     |
| 40         | 2830 | 3260 | 3690 | 4000 | 4370 | 4860 | 5230 | 5720 | 6150 | -     | -     |
| 30         | 3030 | 3495 | 3955 | 4285 | 4680 | 5205 | 5600 | 6125 | 6585 | -     | -     |
| 10 LT      | 3795 | 4370 | 4950 | 5360 | 5855 | 6515 | 7010 | 7670 | 8245 | -     | -     |
| 10 HT      | 3030 | 3495 | 3955 | 4285 | 4680 | 5205 | 5600 | 6125 | 6585 | -     | -     |
| 10 Cyc     | -    | 5240 | 5930 | 6425 | 7015 | 7810 | 8400 | 9190 | 9880 | 10010 | 10455 |

Printed on 18/05/2024 19:44

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..