

AGRIMAX RT 600 - Especificaciones técnicas

Description

AGRIMAX RT 600 es el neumático ideal para utilizarlo en cubiertas herbáceas y actividades de cosecha y pulverización. Gracias a su amplia área de contacto, AGRIMAX RT 600 garantiza una óptima distribución de la presión sobre el terreno reduciendo los daños de prados y protege el suelo. Gracias a la tecnología con hombro redundado, la banda de rodamiento reforzada y el número mayor de tacos, el neumático asegura una grande estabilidad y excelente tracción.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Cosechadora • Esparcidor • Tractor



Version	STANDARD
Type	TL
Tyre Size	750/70 R 26
LI/SS	172 A8/B

Dimensions US Standard

Usa code	94073146
Section Width (inch)	30.7
Overall Diameter (inch)	68.9
Static Loaded Radius (inch)	30.9
Rolling Circumference (inch)	207.4
Rim Rec	DW 25 B
Rim Alt	DW 24 B
ECE	E11-106R-007934

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35	41	46	52
30	5970	6940	7930	8900	9780	10840	11950	12640	13890	-	-
25	5970	6940	7930	8900	9780	10840	11950	12640	13890	-	-
20	6400	7440	8490	9520	10570	11610	12800	13550	14880	-	-
5 LT	8010	9310	10630	11930	13230	14540	16030	16950	18630	-	-
5 HT	6400	7440	8490	9520	10570	11610	12800	13550	14880	-	-
5 Cyc	-	11170	12730	14290	15850	17420	19200	20310	22320	22670	23610

Printed on 18/05/2024 21:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..