

AGRIMAX TURF RT 333 - Especificaciones técnicas



Description

El AGRIMAX TURF RT 333 (R-3+) es un neumático radial diseñado para pequeños tractores utilizados para aplicaciones de jardinería, viñedos y huertos. Su diseño de hombro redondeado ofrece una baja compactación del suelo y lo hace extremadamente delicado sobre el terreno. Su exclusiva banda de rodadura extraprofunda (R-3+) y el diseño especial con bloques direccionales ofrecen una excelente tracción tanto en el campo como en carretera, así como una mayor duración del ciclo de vida útil del neumático. El AGRIMAX TURF RT 333 (R-3+) garantiza unas magníficas propiedades de autolimpieza y, gracias a su reducida resistencia a la rodadura, permite un significativo ahorro de combustible.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Maquina para la recogida de fruta •
Minitractor • Vendimiadora

Version	STANDARD
Type	TL
Tyre Size	260/70 R 16
LI/SS	109 A8/109 B

Dimensions US Standard

Usa code	94067909
Section Width (inch)	10.2
Overall Diameter (inch)	30.3
Static Loaded Radius (inch)	13.7
Rolling Circumference (inch)	90
Rim Rec	W 8
Rim Alt	W 8 L ; W 9
ECE	E11-106R-007158

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
30	1070	1240	1420	1600	1780	1970	2140	2280
25	1070	1240	1420	1600	1780	1970	2140	2280
20	1150	1330	1530	1710	1910	2110	2300	2440
5 LT	1450	1660	1900	2140	2400	2640	2880	3060
5 HT	1150	1330	1530	1710	1910	2110	2300	2440

Printed on 19/05/2024 1:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..