

AGRIMAX TURF RT 333 - Especificaciones técnicas



Description

El AGRIMAX TURF RT 333 (R-3+) es un neumático radial diseñado para pequeños tractores utilizados para aplicaciones de jardinería, viñedos y huertos. Su diseño de hombro redondeado ofrece una baja compactación del suelo y lo hace extremadamente delicado sobre el terreno. Su exclusiva banda de rodadura extraprofunda (R-3+) y el diseño especial con bloques direccionales ofrecen una excelente tracción tanto en el campo como en carretera, así como una mayor duración del ciclo de vida útil del neumático. El AGRIMAX TURF RT 333 (R-3+) garantiza unas magníficas propiedades de autolimpieza y, gracias a su reducida resistencia a la rodadura, permite un significativo ahorro de combustible.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Maquina para la recogida de fruta •
Minitractor • Vendimiadora

| | |
|-----------|--------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 280/70 R 16 |
| LI/SS | 112 A8/112 B |

Dimensions International Standard

| | |
|----------------------------|-----------------|
| Section Width (mm) | 289 |
| Overall Diameter (mm) | 800 |
| Static Loaded Radius (mm) | 359 |
| Rolling Circumference (mm) | 2371 |
| SRI (mm) | 390 |
| Rim Rec | W9 |
| Rim Alt | W 8 ; W 10 |
| ECE | E11-106R-006472 |

Load capacity (Kg)

| km/h / bar | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 | 2.4 |
|------------|-----|-----|-----|------|------|------|------|------|
| 50 | 530 | 605 | 695 | 785 | 875 | 965 | 1055 | 1120 |
| 40 | 530 | 605 | 695 | 785 | 875 | 965 | 1055 | 1120 |
| 30 | 565 | 650 | 745 | 840 | 940 | 1035 | 1130 | 1200 |
| 10 LT | 710 | 815 | 935 | 1055 | 1175 | 1295 | 1415 | 1505 |
| 10 HT | 565 | 650 | 745 | 840 | 940 | 1035 | 1130 | 1200 |

Printed on 19/05/2024 1:25

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..