

AT 625 - Especificaciones técnicas



Description

AT 625 es idóneo para instalarlo en las ternas y las palas compactas que se utilizan en todas las operaciones de excavación y carga en el ámbito agrícola. La banda de rodadura extra profunda garantiza una incrementada resistencia a la perforación y una mayor durabilidad. AT 625 ofrece una excelente tracción y estabilidad, así como una mejor resistencia a los cortes y los desgarros.

UM

International Standard

Construction

 BIAS

Machinery

Industrial: Cargadora retroexcavadora • Cargadora compacta

| | |
|-----------|------------|
| Version | INDUSTRIAL |
| Type | TL |
| Tyre Size | 16.9 - 28 |
| LI/SS | 152 A8 |

Dimensions International Standard

| | |
|----------------------------|---------|
| Ply Rating | 12 |
| Section Width (mm) | 450 |
| Overall Diameter (mm) | 1415 |
| Static Loaded Radius (mm) | 645 |
| Rolling Circumference (mm) | 4254 |
| Rim Rec | DW 15 L |
| Rim Alt | DW 14 L |
| TRA Code | R4 |

Load capacity (Kg)

| | |
|------------|------|
| km/h / bar | 2.60 |
| 40 | 3550 |

Printed on 19/05/2024 15:32

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..