

## EARTHMAX SR 41 - Especificaciones técnicas



### Description

EARTHMAX SR 41 es un neumático radial ideal para las palas cargadoras y los buldóceros en las aplicaciones de transporte, carga y empuje. Gracias a su estructura All Steel y al dibujo de bloques, EARTHMAX SR 41 ofrece una excelente resistencia a los pinchazos y una duración prolongada. Además de muchas horas operativas sin paradas de la máquina, este neumático asegura un confort excepcional. EARTHMAX SR 41 (E-4/L-4) es un neumático radial All Steel ideal para volquetes articulados, palas cargadoras y excavadoras.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Volquete articulado • Buldócer • Pala cargadora • Volquete de perfil bajo

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	23.5 R 25
LI/SS	185 B/195 A2

## Dimensions US Standard

Usa code	94053353
TMPH	110
Overall Width (inch)	24.2
Overall Diameter (inch)	63.4
Static Loaded Radius (inch)	28.5
Rolling Circumference (inch)	188.6
Rim Rec	19.50/2.5
Star Rating	**/*
TRA Code	E4/L4

## Load capacity (lbs)

mph / psi	58	62	65	69	73	76
30	16500	17100	18200	18700	19800	20400
5	22700	23400	24700	25400	26800	-

Printed on 18/05/2024 23:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..