

## EARTHMAX SR 44 - Especificaciones técnicas



### Description

EARTHMAX SR 44 es un neumático radial **All Steel** idóneo para una amplia serie de aplicaciones, incluidas las realizadas en el sector minero, forestal y del transporte. El robusto dibujo de la banda de rodadura E-4 asegura una excelente tracción y confort para el operador. EARTHMAX SR 44 (E-4) puede optimizar la productividad, cualquiera que sea la operación que haya que realizar.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Volquete

Version	STANDARD
Type	TT
Tyre Size	7.50 R 16
LI/SS	122/118 G

## Dimensions US Standard

Usa code	94055005
Overall Width (inch)	8.9
Overall Diameter (inch)	32.3
Static Loaded Radius (inch)	15
Rolling Circumference (inch)	96.5
Rim Rec	6
Rim Alt	5.5, 6.5

## Load capacity (lbs)

mph / psi	105
55 LS	3305
55 LD	2910

Printed on 19/05/2024 1:06

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..