

FL 630 ULTRA - Especificaciones técnicas



Description

FL 630 ULTRA es un neumático de flotación idóneo para utilizarlo tanto en el campo como por carretera, con remolques, auto cisternas y pulverizadores. Gracias al talón reforzado y el dibujo particular de la banda de rodadura, el neumático es ideal para un uso polivalente en cualquier terreno y por carretera. FL 630 ULTRA es sinónimo de una compactación del suelo extraordinariamente reducida.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Esparcidor • Camión cisterna • Remolque

Version	STANDARD
Type	TL
Tyre Size	500/60 R 22.5
LI/SS	155 D/166 A8

Dimensions US Standard

Usa code	94046065
Section Width (inch)	19.8
Overall Diameter (inch)	46.1
Static Loaded Radius (inch)	20.5
Rolling Circumference (inch)	141.4
Rim Rec	AG 16.00
Rim Alt	15.00 ; 16.00 ; 17.00
ECE	E4-106R-001404

Load capacity (lbs)

mph / psi	12	15	17	23	29	35	41	46	52	58
45	2490	2890	3270	3920	4600	5260	5890	6550	7160	7780
40	2730	3160	3590	4300	5050	5750	6460	7180	7860	7540
30	3320	3840	4340	5170	6110	6970	7800	8690	9510	10340
25	3750	4330	4920	5910	6860	7850	8800	9790	10760	11680
15	4320	5000	5680	6790	7970	9060	10210	11310	12420	13500
5	4930	5700	6460	7720	9040	10360	11570	12900	14150	15380

Printed on 19/05/2024 19:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..