

AGRIMAX FORCE - Spécifications techniques



Description

AGRIMAX FORCE, le produit phare de BKT, est un pneu radial spécialement conçu pour les applications de traitement du terrain, de transport et de récolte avec des tracteurs de grande puissance, auxquels il assure un maximum de performances et d'efficacité. Conçu avec la technologie IF, ce pneu supporte des charges lourdes avec de pressions de gonflage plus basses par rapport à un pneu standard. AGRIMAX FORCE se distingue de par une tringle renforcée en assurant une traction excellente, des excellentes qualités d'autonettoyage, une consommation réduite de carburant ainsi qu'une expérience confortable de conduite.;

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Moissonneuse • Tracteur de forte puissance

Version	SPECIAL
Type	TL
Tyre Size	IF 710/75 R 42 CFO
LI/SS	181 D

Dimensions US Standard

Usa code	94060085
Section Width (inch)	28.2
Overall Diameter (inch)	84
Static Loaded Radius (inch)	38.1
Rolling Circumference (inch)	252.1
Rim Rec	DW 25 B
Rim Alt	DW 23 B
ECE	E11-106R-006490
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
45	7790	8930	10250	11580	12910	14230	15550	16540
From 40 to 25	8540	9820	11280	12730	14190	15640	17100	18200
20	8880	10210	11720	13240	14750	16260	17780	18910
12	9230	10600	12170	13750	15310	16890	18460	19640
5	10850	12470	14320	16160	18010	19860	21700	23090
Upto 20 Cyc	11100	12760	14650	16540	18440	20330	22220	23640
Upto 10 Cyc	13240	15220	17470	19730	21980	24240	26500	28180
Upto 5 Cyc	14520	16690	19170	21640	24110	26590	29060	30920
5 HT	8880	10210	11720	13240	14750	16260	17780	18910

Printed on 18/05/2024 18:18

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..