

AGRIMAX RT 600 - Spécifications techniques

Description

AGRIMAX RT 600 est le pneu idéal pour les pelouses et les applications récolte et pulvérisation. Grâce à sa large zone de contact, AGRIMAX RT 600 garantit une répartition optimisée de la pression sur le terrain en réduisant les dommages sur les prairies et en protégeant le sol. Grâce à la technologie avec épaulement arrondi, la tringle renforcée et un nombre augmenté de crampons, ce pneu garantit une grande stabilité et une traction excellente.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Moissonneuse • Épandeur • Tracteur



| | |
|-----------|---------------------|
| Version | STEEL BELTED |
| Type | TL |
| Tyre Size | IF 1250/50 R 32 CFO |
| LI/SS | 201 B |

Dimensions International Standard

| | |
|----------------------------|------------------------|
| Section Width (mm) | 1247 |
| Overall Diameter (mm) | 2063 |
| Static Loaded Radius (mm) | 897 |
| Rolling Circumference (mm) | 6136 |
| SRI (mm) | 975 |
| Rim Rec | DH44B/1.3 (multipiece) |
| ECE | E11-106R-006958 |

Load capacity (Kg)

| km/h / bar | 0.8 | 1.0 | 1.4 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.4 | 3.8 |
|-------------------------------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 50 | 6525 | 7395 | 9280 | 10295 | 11455 | 12325 | 13485 | 14500 | --- | --- |
| 40 | 7115 | 8065 | 10120 | 11225 | 12490 | 13435 | 14700 | 15805 | --- | --- |
| 30 | 7615 | 8630 | 10830 | 12010 | 13365 | 14380 | 15735 | 16915 | --- | --- |
| 10 LT | 9535 | 10805 | 13560 | 15040 | 16735 | 18005 | 19700 | 21180 | --- | --- |
| 10 HT | 7615 | 8630 | 10830 | 12010 | 13365 | 14380 | 15735 | 16915 | --- | --- |
| Upto 10 Cyc with front loader | --- | 11960 | 15320 | 16795 | 19485 | 21365 | 23380 | 25395 | 25800 | 26870 |

* For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Printed on 19/05/2024 12:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..