

EARTHMAX SR 44 - Spécifications techniques



Description

EARTHMAX SR 44 est un pneu radial **All Steel** (Tout Acier) adapté pour une série d'applications y compris les opérations dans les mines, les forêts ou de transport. Le dessin robuste de la bande de roulement E-4 assure une excellente traction et un grand confort pour l'opérateur. EARTHMAX SR 44 (E-4) est en mesure d'optimiser la productivité, quelle que soit votre opération.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Camion à benne basculante

Version	STANDARD
Type	TT
Tyre Size	12.00 R 24 (325/95 R 24)
LI/SS	158 B

Dimensions US Standard

Usa code	94034284
TMPH	96
Overall Width (inch)	12.2
Overall Diameter (inch)	49.2
Static Loaded Radius (inch)	22.6
Rolling Circumference (inch)	149.2
Rim Rec	8.50V
Rim Alt	9.00V
Star Rating	***
TRA Code	E4

Load capacity (lbs)

mph / psi	65	69	73	76	80	83	87	91	94	98	102
30	6800	6950	7400	7600	7850	8050	8250	8550	8800	9100	9350

Printed on 19/05/2024 03:53

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..