

EARTHMAX SR 45 M - Spécifications techniques

Description

EARTHMAX SR 45 M est un pneu radial **All Steel** (Tout Acier) particulièrement conçu pour les tombereaux rigides. EARTHMAX SR 45 M assure une excellente traction et il est idéal pour les opérations sur longues distances.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Tombereau rigide



| | |
|-----------|------------------------|
| Version | CUT RESISTANT COMPOUND |
| Type | TL |
| Tyre Size | 24.00 R 35 |
| LI/SS | 209 B |

Dimensions US Standard

| | |
|------------------------------|-----------|
| Usa code | 94029907 |
| TMPH | 228 |
| Overall Width (inch) | 26.1 |
| Overall Diameter (inch) | 85.8 |
| Static Loaded Radius (inch) | 38.6 |
| Rolling Circumference (inch) | 257.4 |
| Rim Rec | 17.00/3.5 |
| Rim Alt | -- |
| Star Rating | ** |
| TRA Code | E4 |

Load capacity (lbs)

| mph / psi | 73 | 76 | 80 | 83 | 87 | 91 | 94 | 98 | 102 |
|-----------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 30 | 30900 | 32000 | 34200 | 35300 | 36400 | 37500 | 38600 | 39700 | 40800 |

Printed on 19/05/2024 11:05

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..