

## FL 695 - Fiche de données



### Description

Le FL 695 a été spécialement conçu pour les remorques dans les secteurs de la construction et du transport avec une bande de roulement unique à bloc central. Grâce à sa carcasse robuste, le FL 695 peut transporter de lourdes charges sans impact sur la stabilité quelles que soient les conditions, et sa bande de roulement profonde assure un auto-nettoyage optimal sur route et hors route. De multiples couches de câble d'acier renforcent cette sculpture contre les crevaisons.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agriculture: Remorque

Industriel: Remorque

SIZE	Version	LI/SS	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
<b>600/55 R 26.5</b>	STEEL BELTED	173 D			AG20.00		591	1335	620	4090	625	TL	E11-106R-007937
<b>650/55 R 26.5</b>	STEEL BELTED	178 D			AG20.00	AG22.00	630	1390	630	4242	675	TL	E11-106R-007052
<b>600/60 R 30.5</b>	STEEL BELTED	179 D	179 D	179 D	AG20.00		611	1495	693	4586	725	TL	E11-106R-008503
<b>710/50 R 30.5</b>	STEEL BELTED	177 D	177 D	177 D	AG24.00	AG20.00	700	1490	691	4553	700	TL	E11-106R-008661

Printed on 18/05/2024 21:45

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..