

## MULTIMAX MP 527 - Spécifications techniques



### Description

MULTIMAX MP 527 est un pneu radial polyvalent pour chargeurs télescopiques et chargeuses compactes dans les applications agro-industrielles. Ce pneu présente un dessin à blocs de la bande de roulement qui garantit une excellente traction même sur les surfaces dures. Le flanc robuste du pneu assure une stabilité exceptionnelle en mode levage. MULTIMAX MP 527 est réalisé avec un mélange particulièrement résistant aux coupures et déchirures, ce qui se traduit par une longue vie du pneu.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agriculture: Chargeuse compacte • Chargeuse télescopique

Industriel: Chargeuse compacte • Chargeuse télescopique

|           |                 |
|-----------|-----------------|
| Version   | STANDARD        |
| Type      | TL              |
| Tyre Size | 400/80 R 24 IND |
| LI/SS     | 162 A8/B        |

## Dimensions International Standard

|                            |                           |
|----------------------------|---------------------------|
| Section Width (mm)         | 404                       |
| Overall Diameter (mm)      | 1250                      |
| Static Loaded Radius (mm)  | 578                       |
| Rolling Circumference (mm) | 3834                      |
| SRI (mm)                   | 600                       |
| Rim Rec                    | DW 13                     |
| Rim Alt                    | DW 12 ; DW 13 L ; DW 14 L |
| ECE                        | E11-106R-002982           |

## Load capacity (Kg)

| km/h / bar | 1.6  | 2.0  | 2.4  | 2.8  | 3.2  | 3.4  | 3.6  | 4.0  | 4.4  | 4.6  | 4.8  | 5.0   | 5.2   | 5.4   |
|------------|------|------|------|------|------|------|------|------|------|------|------|-------|-------|-------|
| 50         | 1855 | 2185 | 2565 | 2900 | 3230 | 3350 | 3520 | 3895 | 4220 | 4435 | 4540 | 4750  | -     | -     |
| 40         | 1855 | 2185 | 2565 | 2900 | 3230 | 3350 | 3520 | 3895 | 4220 | 4435 | 4540 | 4750  | -     | -     |
| 30         | 1985 | 2340 | 2750 | 3105 | 3460 | 3590 | 3770 | 4170 | 4515 | 4745 | 4860 | 5085  | -     | -     |
| 25         | 2060 | 2430 | 2850 | 3220 | 3590 | 3725 | 3910 | 4330 | 4690 | 4925 | 5040 | 5275  | -     | -     |
| 10 Cyc.    | 2280 | 2785 | 3280 | 3850 | 4350 | 4600 | 4845 | 5280 | 5845 | 6090 | 6330 | 6655  | 6810  | 7125  |
| Static     | 3500 | 4270 | 5030 | 5900 | 6670 | 7050 | 7430 | 8100 | 8960 | 9340 | 9710 | 10205 | 10445 | 10925 |

Printed on 19/05/2024 14:10

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..