

## RIDEMAX FL 693 M - Spécifications techniques



### Description

RIDEMAX FL 693 M est le pneu idéal pour les applications de transports fréquents sur route avec des remorques/camions-citernes. Conçu pour l'utilisation 75% sur route, RIDEMAX FL 693 M présente des prestations excellentes sur route et priorise aussi le confort et les propriétés d'auto-nettoyage. L'indice de vitesse classe D/E de la gamme est synonyme de vitesse élevée sur la route avec un gain de temps considérable. La résistance au roulement réduite contribue à l'économie de carburant, tandis que la tringle renforcée et les ceintures en acier assurent une durabilité avancée.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agriculture: Véhicule citerne • Remorque

Version	STANDARD
Type	TL
Tyre Size	560/45 R 22.5
LI/SS	160D

## Dimensions International Standard

Section Width (mm)	543
Overall Diameter (mm)	1076
Static Loaded Radius (mm)	491
Rolling Circumference (mm)	3306
SRI (mm)	525
Rim Rec	AG 16.00
ECE	E11-106R-009052

## Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.5	5.0	5.5	6.0
70	990	1320	1650	1860	2145	2435	2685	2930	3220	3425	3630	3880	4125
65	1080	1440	1800	2025	2340	2655	2925	3195	3510	3735	3960	4230	4500
50	1310	1745	2180	2455	2835	3215	3540	3870	4250	4520	4795	5120	5445
40	1470	1960	2450	2755	3185	3615	3980	4350	4775	5080	5390	5755	6120
30	1635	2175	2720	3060	3535	4010	4420	4825	5305	5640	5980	6390	6795
25	1710	2280	2845	3200	3700	4195	4625	5050	5550	5905	6260	6685	7110
10	1945	2595	3240	3645	4215	4780	5265	5755	6320	6725	7130	7615	8100

Printed on 19/05/2024 04:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..