

## RIDEMAX FL 693 M - Spécifications techniques



### Description

RIDEMAX FL 693 M est le pneu idéal pour les applications de transports fréquents sur route avec des remorques/camions-citernes. Conçu pour l'utilisation 75% sur route, RIDEMAX FL 693 M présente des prestations excellentes sur route et priorise aussi le confort et les propriétés d'auto-nettoyage. L'indice de vitesse classe D/E de la gamme est synonyme de vitesse élevée sur la route avec un gain de temps considérable. La résistance au roulement réduite contribue à l'économie de carburant, tandis que la tringle renforcée et les ceintures en acier assurent une durabilité avancée.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agriculture: Véhicule citerne • Remorque

Version	STANDARD
Type	TL
Tyre Size	600/60 R 30.5
LI/SS	169 D

## Dimensions International Standard

Section Width (mm)	605
Overall Diameter (mm)	1495
Static Loaded Radius (mm)	681
Rolling Circumference (mm)	4495
SRI (mm)	725
Rim Rec	AG 20.00
Rim Alt	AG 18.00
ECE	E11-106R-006160

## Load capacity (Kg)

km/h / bar	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1930	2165	2695	3065	3540	4015	4385	4805	5280
65	2120	2380	2960	3365	3890	4410	4815	5280	5800
50	2565	2880	3585	4075	4705	5340	5830	6390	7020
40	2880	3235	4025	4580	5290	6000	6550	7180	7890
30	3200	3595	4470	5085	5870	6660	7275	7975	8760
25	3350	3760	4675	5320	6145	6970	7610	8345	9165
10	3815	4285	5325	6060	6995	7935	8670	9505	10440

Printed on 19/05/2024 06:14

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..