

AGRIMAX RT 765M - Data Sheet



Description

AGRIMAX RT 765M, a BKT 70 series tire, is suitable for cutting-edge tractors for several heavy-duty applications such as soil tillage, field and road transport, vineyard harvesting, and spraying. A wide contact patch ensures the best possible traction and comfort on all surfaces at any time. This tire provides great self-cleaning properties and reduced soil compaction. Two sizes are available with steel-belted technology.

UM

US Standard

Construction



Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

SIZE	Version	USACode	TRA Code	LI/SS	RIM REC	RIM ALT	sw	OD	SLR	RC	Туре	ECE
710/70 R 38	SPECIAL	94066780	R1W	166 D	DW 23 B		28.2	77.1	33.8	226.4	TL	E11-106R-005837
710/70 R 38	SPECIAL	94066810	R1W	175D/178A8	DW 23 B		28.2	77.1	33.8	226.4	TL	E11-106R-006000
710/70 R 38	STANDARD	94066803	R1W	175D/178A8	DW 23 B	DW 25 B	28.2	77.1	33.8	226.4	TL	E11-106R-006000
710/70 R 38	STANDARD	94066797	R1W	171D/174A8	DW 23 B		28.2	77.1	33.8	226.4	TL	E11-106R-004072
710/70 R 38	STANDARD	94066773	R1W	166 D	DW 23 B	DW 25 B	28.2	77.1	33.8	226.4	TL	E11-106R-005837
710/70 R 42	SPECIAL	94066483	R1W	176 D/179 A8	DW 23 B	DW 25 B	28.2	81.1	36.3	243.1	TL	E11-106R-006001
710/70 R 42	SPECIAL	94066476	R1W	173D/176A8	DW 23 B	DW 25 B	28.2	81.1	36.3	243.1	TL	E11-106R-006018
710/70 R 42	STANDARD	94066469	R1W	176D/179A8	DW 23 B	DW 25 B	28.2	81.1	36.3	243.1	TL	E11-106R-006001
710/70 R 42	STANDARD	94066452	R1W	173D/176A8	DW 23 B	DW 25 B	28.2	81.1	36.3	243.1	TL	E11-106R-006018

Printed on 19/05/2024 11:41

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..