

AGRIMAX V-FLECTO - Technical Specifications



Description

AGRIMAX V-FLECTO is BKT's response to the challenging demand of both technology and performance for high-power tractors. This tire is perfect for soil tillage and haulage applications thanks to reduced soil compaction and self-cleaning properties. With the exclusive VF technology, AGRIMAX V-FLECTO can carry heavy loads with a lower inflating pressure compared to standard and IF tires, reaching high speeds. It also features the Narrow Rim Option that allows mounting standard rims on the tire. BKT has designed this tire with optimized geometry to enhance driving comfort both in the fields and on the road reducing fuel consumption.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: High-Power Tractor

Version	STANDARD
Type	TL
Tyre Size	VF 600/60 R 28 NRO
LI/SS	157 D

Dimensions US Standard

Usa code	94058495
Section Width (inch)	23.1
Overall Diameter (inch)	56.7
Static Loaded Radius (inch)	24.9
Rolling Circumference (inch)	166.5
Rim Rec	DW 20 B
Rim Alt	DW 18 L
Narrow Rim option	DW 18 L
ECE	E11-106R-004471
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23
45	4540	5290	6030	6780	7520	8270
from 40 to 25	4990	5820	6640	7450	8270	9095
20	5090	5930	6770	7590	8430	9270
12	5190	6050	6900	7750	8600	9460
5	5490	6390	7300	8190	9090	10000
*Upto 5 Cyc with front loader	6990	8150	9280	10430	11570	12730
5 HT	5090	5930	6770	7590	8430	9270

* *For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Printed on 18/05/2024 19:41

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..