



## EARTHMAX SR 44 - Data Sheet



### Description

EARTHMAX SR 44 is an **All Steel** radial tire suitable for a variety of applications including mining, haulage and logging applications. The rugged E-4 tread pattern provides both excellent traction and operator comfort. EARTHMAX SR 44 (E-4) is able to optimize productivity whatever your operation is.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: On/Off Truck

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TMPH	ECE
7.50 R 16	STANDARD	94055005			122/118 G	6	5.5, 6.5	8.9	32.3	15	96.5	TT	0	
10.00 R 20	STANDARD	94045075			146/143 G	7.50	7.0; 7.50VM; 8.0	10.6	42.3	19.9	126	TT	0	E11-54R-0015908
11.00 R 20	STANDARD	94046706	E4	***		8.00	7.50; 8.50;8.50VM	11.1	43.7	20.5	131	TT	0	
12.00 R 20	STANDARD	94052295	E4	***		8.50V	9.00V	12	44.8	20.9	134.2	TT	0	
12.00 R 24 (325/95 R 24)	STANDARD	94034284	E4	***	158 B	8.50V	9.00V	12.2	49.2	22.6	149.2	TT	96	
325/95 R 24 (12.00 R 24)	STANDARD	94039791	E4	***	158 B	8.50V	9.00V	12.2	49.2	22.6	149.2	TT	96	
325/95 R 24 (12.00 R 24)	STANDARD	94054282	E4	***	158 B	8.50V	9.00V	12.2	49.2	22.6	149.2	TL	96	

Printed on 19/05/2024 15:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..