

MULTIMAX MP 527 - Technical Specifications



Description

MULTIMAX MP 527 is a multi-purpose radial tire designed for telehandlers and compact loaders in agro-industrial applications. The tire shows a block pattern design providing excellent traction even on the harder surfaces. The strong sidewall ensures outstanding stability in lift mode. MULTIMAX MP 527 is made of a special cut-and-chip-resistant compound providing and a long service life.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Compact Loader • Telehandler
Industrial: Compact Loader • Telehandler

Version	STANDARD
Type	TL
Tyre Size	460/70 R 24 IND (17.5L R 24)
LI/SS	159 A8/B

Dimensions US Standard

Usa code	94052097
Section Width (inch)	18.3
Overall Diameter (inch)	49.4
Static Loaded Radius (inch)	22.6
Rolling Circumference (inch)	149.6
Rim Rec	DW 15 L
Rim Alt	DW 14 L ; DW 16 L
ECE	E11-106R-002983

Load capacity (lbs)

mph / psi	23	29	35	41	46	51	58	61	64
30	4630	5500	6270	7140	8010	8590	9640	-	-
25	4630	5500	6270	7140	8010	8590	9640	-	-
20	4960	5900	6720	7650	8580	9190	10330	-	-
15	5150	6120	6970	7940	8900	9550	10710	-	-
5 Cvc.	5650	6960	8180	9410	10710	11650	13170	13900	14470
Static	8660	10660	12540	14430	16420	17870	20190	21310	22190

Printed on 19/05/2024 11:59

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..