

BK-LOADER 53 - Specifiche tecniche



Description

BK-LOADER 53 è uno pneumatico con cinture in aramide sviluppato per pale cariatrici in applicazioni industriali. Lo speciale disegno del battistrada garantisce ottima stabilità laterale oltre a straordinaria resistenza all'usura, a tagli e perforazioni grazie al battistrada extra profondo. BK-LOADER 53 si distingue per le eccezionali proprietà di autopulitura nonché grip e trazione eccellenti su superfici bagnate e asciutte. Lo pneumatico è particolarmente idoneo per operazioni di recycling.

UM

US Standard

Construction

 RADIAL

Machinery

Industriale: Pala caricatrice

Version	ARAMID BELTED
Type	TL
Tyre Size	365/70 R 18
LI/SS	146A2/142A4

Dimensions US Standard

Usa code	94074143
Section Width (inch)	14.2
Overall Diameter (inch)	39
Static Loaded Radius (inch)	18
Rolling Circumference (inch)	118.8
Rim Rec	11

Load capacity (lbs)

mph / psi	22	29	36	44	51	58	65	73	80
12	2060	2640	3100	3580	4090	4510	4980	5380	5850
5	2320	2980	3510	4040	4630	5100	5630	6090	6620
STATIC	3690	4740	5580	6420	7370	8110	8940	9680	10520

Printed on 18/05/2024 17:41

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..