

EARTHMAX SR 313 - Specifiche tecniche



Description

EARTHMAX SR 313 è uno pneumatico radiale All Steel specificamente progettato per dumper articolati e pale che operano in condizioni rocciose difficili. La sua mescola resistente al taglio e lo speciale design del battistrada proteggono da tagli e danni, insieme alle proprietà autopulenti. Il design quadrato della spalla massimizza il contatto con il suolo per un'eccellente manovrabilità. La costruzione radiale All Steel con cinghie in acciaio multistrato garantisce una maggiore durata. EARTHMAX SR 313 è lo pneumatico ideale per operazioni di carico e trasporto.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Dumper articolato • Pala caricatrice

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	15.5 R 25
LI/SS	160 B/169 A2

Dimensions International Standard

TKPH	135
Overall Width (mm)	394
Overall Diameter (mm)	1265
Static Loaded Radius (mm)	566
Rolling Circumference (mm)	3822
Rim Rec	12.00/1.3
Star Rating	**/*
TRA Code	E3/L3

Load capacity (Kg)

km/h / bar	4.00	4.25	4.50	4.75	5.00	5.25
50	3650	3875	4000	4250	4375	4500
10	5000	5150	5450	5600	5800	-

Printed on 19/05/2024 01:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..