

## EARTHMAX SR 44 - Specifiche tecniche



### Description

EARTHMAX SR 44 è uno pneumatico radiale **All Steel** idoneo per una serie di applicazioni incluse operazioni in miniera, di trasporto e forestiere. Il robusto disegno del battistrada E-4 assicura eccellente trazione e comfort per l'operatore. EARTHMAX SR 44 (E-4) è in grado di ottimizzare la produttività, qualunque sia la vostra operazione.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Carro con cassone ribaltabile

Version	STANDARD
Type	TL
Tyre Size	325/95 R 24 (12.00 R 24)
LI/SS	158 B

## Dimensions US Standard

Usa code	94054282
TMPH	96
Overall Width (inch)	12.2
Overall Diameter (inch)	49.2
Static Loaded Radius (inch)	22.6
Rolling Circumference (inch)	149.2
Rim Rec	8.50V
Rim Alt	9.00V
Star Rating	***
TRA Code	E4

## Load capacity (lbs)

mph / psi	65	69	73	76	80	83	87	91	94	98	102
30	6800	6950	7400	7600	7850	8050	8250	8550	8800	9100	9350

Printed on 18/05/2024 20:58

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..