

FL 630 ULTRA - Scheda tecnica



Description

FL 630 ULTRA è idoneo per rimorchi, autobotti e spargitori. Grazie al tallone rinforzato e al particolare disegno del battistrada, è lo pneumatico ideale per un utilizzo polivalente su ogni tipo di terreno o su strada. FL 630 ULTRA è sinonimo di compattazione del terreno straordinariamente ridotta.

UM

US Standard

Construction

 RADIAL

Machinery

Agricoltura: Spargitore • Autobotte • Rimorchio

SIZE	Version	USACode	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
500/60 R 22.5	STANDARD	94046065	155 D/166 A8	AG 16.00	15.00 ; 16.00 ; 17.00	19.8	46.1	20.5	141.4	TL	E4-106R-001404
560/45 R 22.5	STANDARD	94052790	152 D/163 A8	AG 16.00		21.4	42.4	19.3	129.5	TL	E11-106R-003012
560/60 R 22.5	STANDARD	94052509	161 D/172 A8	AG 16.00	16.00 ; 17.00 ; AG 20.00	21.4	49	21.1	148	TL	E11-106R-003013
600/50 R 22.5	STANDARD	94054220	159 D/170 A8	AG 20.00		24.1	46.1	20.4	139.1	TL	E11-106R-003960
710/40 R 22.5	STANDARD	94052905	161 D/172 A8	AG 24.00		28.6	44.9	20.2	137.4	TL	E11-106R-003016
600/55 R 26.5	STANDARD	94044955	165 D/176 A8	AG 20.00		24.1	52.5	22.8	160.2	TL	E11-106R-006813
650/55 R 26.5	STANDARD	94044269	169 D/180 A8	AG 20.00		25.4	54.7	23.6	165.6	TL	E11-106R-006814
710/50 R 26.5	STANDARD	94047284	170 D/181 A8	AG 24.00	AG 20.00	28.6	54.4	23.6	165.7	TL	E11-106R-006812
800/45 R 26.5	STANDARD	94054831	174 D/184 A8	AG 28.00	AG 24.00	32.6	54.8	24.3	166.9	TL	E11-106R-004074

Printed on 18/05/2024 22:14

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..