

RIDEMAX FL 693 M - Specifiche tecniche



Description

RIDEMAX FL 693 M è lo pneumatico ideale per chi deve percorrere frequentemente tratti stradali con rimorchi/autobotti. Sviluppato per un utilizzo del 75% su strada, RIDEMAX FL 693 M mostra delle prestazioni eccellenti su strada, dando la priorità al comfort e alle proprietà di autopulitura. L'indice di velocità classe D/E della gamma è sinonimo di velocità più elevate sui percorsi stradali con significativo risparmio di tempo. La bassa resistenza al rotolamento contribuisce ad un consumo minore di carburante, mentre il tallone rinforzato e le cinture in acciaio garantiscono una durabilità superiore.

UM

US Standard

Construction

 RADIAL

Machinery

Agricoltura: Autobotte • Rimorchio

Version	STANDARD
Type	TL
Tyre Size	560/55 R 22.5
LI/SS	158 D/155 E

Dimensions US Standard

Usa code	94037353
Section Width (inch)	21.4
Overall Diameter (inch)	46.5
Static Loaded Radius (inch)	21
Rolling Circumference (inch)	142.3
Rim Rec	AG 16.00
Rim Alt	17.00 ; 20.00
ECE	E4-106R-000631

Load capacity (lbs)

mph / psi	15	17	23	29	35	41	46	52	58
45	3160	3590	4280	5050	5780	6420	7180	7860	8540
40	3470	3940	4680	5530	6330	7030	7870	8620	9370
30	4210	4770	5680	6700	7660	8510	9530	10440	11340
25	4720	5360	6370	7530	8610	9560	10710	11730	12740
15	5490	6230	7410	8740	10000	11110	12440	13620	14800
5	6250	7090	8430	9950	11390	12650	14170	15520	16860

Printed on 18/05/2024 21:43

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..