

RIDEMAX FL 693 M - Specifiche tecniche



Description

RIDEMAX FL 693 M è lo pneumatico ideale per chi deve percorrere frequentemente tratti stradali con rimorchi/autobotti. Sviluppato per un utilizzo del 75% su strada, RIDEMAX FL 693 M mostra delle prestazioni eccellenti su strada, dando la priorità al comfort e alle proprietà di autopulitura. L'indice di velocità classe D/E della gamma è sinonimo di velocità più elevate sui percorsi stradali con significativo risparmio di tempo. La bassa resistenza al rotolamento contribuisce ad un consumo minore di carburante, mentre il tallone rinforzato e le cinture in acciaio garantiscono una durabilità superiore.

UM

International Standard

Construction

 RADIAL

Machinery

Agricoltura: Autobotte • Rimorchio

Version	STANDARD
Type	TL
Tyre Size	560/60 R 22.5
LI/SS	165 D/162 E

Dimensions International Standard

Section Width (mm)	543
Overall Diameter (mm)	1244
Static Loaded Radius (mm)	552
Rolling Circumference (mm)	3767
SRI (mm)	600
Rim Rec	AG 16.00
Rim Alt	16.00 ; 17.00 ; AG 20.00
ECE	E4-106R-001403

Load capacity (Kg)

km/h / bar	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	5.0
70	1555	1745	2170	2465	2850	3230	3530	3870	4250	4750
65	1690	1900	2360	2685	3100	3515	3840	4210	4625	5150
50	2050	2300	2860	3250	3755	4260	4650	5100	5600	6235
40	2300	2580	3210	3650	4215	4785	5225	5725	6290	7005
25	2670	3000	3730	4240	4900	5560	6070	6655	7310	8140
10	3040	3415	4250	4830	5580	6330	6910	7580	8325	9270

Printed on 18/05/2024 19:24

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..