

RT 747 AGRO INDUSTRIAL - Specifiche tecniche



Description

RT 747 AGRO INDUSTRIAL è uno pneumatico radiale agro-industriale idoneo per pale compatte e sollevatori telescopici. I ramponi extra larghi assicurano eccellente trazione e straordinaria stabilità nelle operazioni di sollevamento. È stato progettato con una speciale miscela resistente a tagli e lacerazioni che consente allo pneumatico di trasportare carichi pesanti. RT 747 AGRO INDUSTRIAL è la giusta risposta per tutte le operazioni agricole che in generale richiedono una versatilità eccezionale.

UM

International Standard

Construction

 RADIAL

Machinery

Agricoltura: Pala compatta • Sollevatore telescopico
Industriale: Pala compatta • Sollevatore telescopico

Version	STANDARD
Type	TL
Tyre Size	460/70 R 24 (17.5L R 24)
LI/SS	159A8/156B

Dimensions International Standard

Section Width (mm)	465
Overall Diameter (mm)	1254
Static Loaded Radius (mm)	556
Rolling Circumference (mm)	3840
SRI (mm)	575
Rim Rec	DW 15 L
Rim Alt	DW 14 L ; DW 16 L
ECE	E11-106R-005105

Load capacity (Kg)

km/h / bar	1.2	1.6	2.0	2.4	2.8	3.2	3.5	4.0
50	1535	1890	2245	2560	2915	3265	3505	4000
40	1705	2100	2495	2845	3240	3630	3895	4375
30	1775	2185	2595	2960	3370	3775	4050	4550
25	1805	2225	2645	3015	3435	3850	4130	4640
10 Cyc	2560	3150	3745	4270	4860	5445	5845	6565
Static	3920	4830	5740	6545	7450	8350	8960	10065

Printed on 18/05/2024 21:00

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..