

## TR 387 IND - Specifiche tecniche



### Description

TR 387 IND è uno pneumatico industriale, idoneo per rimorchi industriali e compattatori. Lo pneumatico si distingue per l'elevata capacità di carico ed è disponibile in diverse versioni al fine di soddisfare le esigenze specifiche degli utilizzatori in termini di resistenza a tagli e strappi, operazioni di servizio pesante e durabilità. La versione "dual bead", a doppio tallone, è particolarmente idonea per trattori industriali e operazioni di trasporto con rimorchi.

### UM

US Standard

### Construction

❖ BIAS

### Machinery

Industriale: Compattatore • Trattore industriale • Rimorchio

|           |                            |
|-----------|----------------------------|
| Version   | DUAL BEAD                  |
| Type      | TL                         |
| Tyre Size | 620/75 - 30<br>(23.1 - 30) |
| LI/SS     | 157 A8                     |

## Dimensions US Standard

|                         |                   |
|-------------------------|-------------------|
| Usa code                | 94065318          |
| Ply Rating              | 16                |
| Section Width (inch)    | 23.8              |
| Overall Diameter (inch) | 65.9              |
| Rim Rec                 | DW 20 A ; DW 20 B |
| TRA Code                | R3                |

## Load capacity (lbs)

| mph / psi | 34    |
|-----------|-------|
| 20        | 10200 |

Printed on 19/05/2024 04:42

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..