

## AGRIMAX FORCE - Especificações técnicas



### Description

AGRIMAX FORCE, o produto de ponta da BKT, é um pneu radial devidamente projetado para aplicações de tratamento do terreno, de transporte e de colheita com tratores de elevada potência, garantindo máximas prestações e eficiência. Com a tecnologia IF, este pneu permite-lhe transportar cargas pesadas a pressões de enchimento inferiores em comparação com o pneu estandarte reduzindo a compactação do solo. AGRIMAX FORCE é dotado de talão reforçado e assegura uma tração maior, propriedades de autolimpeza e economia de combustível, bem como uma experiência de condução confortável.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agricultura: Ceifeira • Trator de alta potencia

Version	STANDARD
Type	TL
Tyre Size	IF 710/60 R 34 CFO
LI/SS	170 D

## Dimensions US Standard

Usa code	94022229
Section Width (inch)	27.9
Overall Diameter (inch)	67.6
Static Loaded Radius (inch)	30
Rolling Circumference (inch)	201.8
Rim Rec	DW 25 B
ECE	E4-106R-001485
TRA Code	R1W

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
45	5530	6370	7340	8180	9140	9990	11190	12040
from 40 to 25	6080	7010	8070	8990	10050	10980	12300	13200
20	6330	7290	8390	9350	10450	11410	12790	13760
12	6570	7560	8710	9710	10850	11850	13280	14290
5	7730	8900	10240	11420	12760	13930	15620	16800
Upto 20 Cyc	7900	9100	10480	11680	13060	14260	15980	17200
Upto 10 Cyc	9420	10860	12500	13930	15570	17010	19060	20500
Upto 5 Cyc	10340	11920	13710	15290	17080	18660	20910	22490
5 HT	6330	7290	8390	9350	10450	11410	12790	13760

Printed on 19/05/2024 12:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..