

AGRIMAX TERIS - Dados técnicos



Description

As ceifeiras-debulhadoras de elevada potência atuais exigem pneus capazes de suportar máquinas e cargas pesadas sem prejudicar as culturas. A BKT compromete-se a oferecer-lhe soluções de pneus radiais na vanguarda para aumentar o rendimento da sua colheita. AGRIMAX TERIS é o parceiro ideal para as suas operações combinadas. As suas características essenciais são uma tração excelente e uma capacidade de carga elevada que fornecem os melhores desempenhos em termos de operação de colheita. A proteção do flanco e os ombros arredondados contribuem a aumentar a resistência - prolongando portanto o ciclo de vida do produto - também em condições severas e em presença de restolhos no campo.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Colhedora de algodão • Ceifeira

| SIZE | Version | LI/SS | RIM REC | RIM ALT | SW | OD | SLR | RC | SRI | Type | ECE |
|------------------------------------|----------|-----------------|----------------------|---|------|------|-----|------|-----|------|-----------------|
| 620/75 R 26 CHO | STANDARD | 166 A8/B | DW 20 B | | 625 | 1590 | 730 | 4851 | 750 | TL | E4-106R-001419 |
| 750/65 R 26 CHO (28L R 26) | STANDARD | 166 A8/B | DW 25 B | DW 23 B | 764 | 1636 | 713 | 4908 | 750 | TL | E4-106R-000810 |
| 750/65 R 26 CHO (28L R 26) | STANDARD | 171 A8/B | DW 25 B | DW 23 B | 764 | 1636 | 713 | 4908 | 750 | TL | E4-106R-001496 |
| 710/55 R 28 CHO | STANDARD | 164 A8/B | DW 23 B | | 716 | 1493 | 663 | 4442 | 700 | TL | E11-106R-005940 |
| 620/75 R 30 CHO | STANDARD | 168 A8/B | DW 20 B | | 625 | 1692 | 779 | 5169 | 800 | TL | E4-106R-001420 |
| 1050/50 R 32 CHO | STANDARD | 184 A8/181 B | 36.0 VA | | 1059 | 1893 | 840 | 5685 | 875 | TL | E4-106R-000813 |
| 650/75 R 32 CHO | STANDARD | 172 A8/B | DW 21 B | DW 20 B ; DW 23 B | 670 | 1795 | 816 | 5378 | 850 | TL | E4-106R-001425 |
| 800/65 R 32 CHO (30.5L R 32) | STANDARD | 178 A8/175 B | DW 27 B | DW 25 B ; DH 27 B | 818 | 1853 | 838 | 5551 | 875 | TL | E4-106R-001430 |
| 900/60 R 32 CHO | STANDARD | 185 A8/182 B | DW 27 B | DW 28 B ; DW 30 B | 875 | 1910 | 875 | 5775 | 900 | TL | E4-106R-001433 |
| 900/60 R 32 CHO | STANDARD | 181 A8/178 B | DW 27 B | DW 28 B ; DW 30 B | 886 | 1910 | 854 | 5700 | 900 | TL | E4-106R-001431 |
| IF 710/75 R 32 CFO | STANDARD | 183 A8/B | DW 25 B | DW 23 B | 716 | 1879 | 851 | 5653 | 875 | TL | E11-106R-005025 |
| IF 580/80 R 34 CFO | STANDARD | 177 D | DW 20 B ; DW 20 A | DW 21 A ; DW 21 B | 586 | 1792 | 810 | 5422 | 850 | TL | E4-106R-001833 |
| IF 710/75 R 34 CFO | STANDARD | 184 A8/B | DW 25 B | | 716 | 1930 | 870 | 5852 | 900 | TL | E11-106R-004899 |
| 520/85 R 42 | STANDARD | 168 D | DW 16 L | W15L ; DW15L ; DD16L ; W16L ; DD18L ; DW18L ; W18L | 516 | 1951 | 890 | 5851 | 925 | TL | E4-106R-001829 |

Printed on 19/05/2024 16:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..