

## EARTHMAX SR 25 PLUS - Dados técnicos



### Description

EARTHMAX SR 25 PLUS (G-2/L-2) é um pneu radial **All Steel** projetado particularmente para motoniveladoras e carregadores que operam nas aplicações mais severas e nas aplicações de construção rodoviária e de minas. O desenho não direcional do piso do pneu proporciona propriedades excelentes de autolimpeza junto com uma ótima tração e estabilidade e mesmo em terrenos.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Industrial: Trator de esteira • Motoniveladora •  
Carregadora

OTR: Trator de esteira • Motoniveladora • Carregadora

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
14.00 R 24	CUT RESISTANT COMPOUND	G2/L2	*	153 A8/175 A2	8.00TG	9.00GR	359	1372	626	4146	TL

Printed on 19/05/2024 17:21

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..