

## EARTHMAX SR 35 - Dados técnicos



### Description

Earthmax SR 35 é um pneu radial All Steel, dotado de baixo perfil, especialmente projetado para dumper articulados e pás carregadoras. É ideal para operações que exigem uma excelente tração e flutuação. Earthmax SR 35 assegura tanto tração como estabilidade excelentes. Graças à carcaça robusta com cintos em aço, garante uma duração extraordinária para além da resistência contra rasgos e furos.

### UM

International Standard

### Construction

 RADIAL

### Machinery

OTR: Dumper Articulado • Trator de esteira • Carregadora

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TKPH
650/65 R 25 (25/65 R 25)	CUT RESISTANT COMPOUND	E3	**	180 B	19.50/2.5		635	1498	669	4493	TL	202
650/65 R 25 (25/65 R 25)	CUT RESISTANT COMPOUND	E3/L3	**/*	180 B/193 A2	19.50/2.5		635	1498	669	4493	TL	202
650/65 R 25 (25/65 R 25)	CUT RESISTANT COMPOUND	L3	*	193 A2	19.50/2.5		635	1498	669	4493	TL	
750/65 R 25 (30/65 R 25)	CUT RESISTANT COMPOUND	E3	**	190 B	24.00/3.0	22.00/3.0,25.00/3.0	740	1601	715	4802	TL	223
750/65 R 25 (30/65 R 25)	CUT RESISTANT COMPOUND	E3/L3	**/*	190 B/202 A2	24.00/3.0	22.00/3.0 ; 25.00/3.0	740	1601	715	4802	TL	223
750/65 R 25 (30/65 R 25)	CUT RESISTANT COMPOUND	L3	**	209 A2	24.00/3.0	22.00/3.0,25.00/3.0	740	1601	715	4802	TL	
775/65 R 29	CUT RESISTANT COMPOUND	E3/L3	**/*	195 B/206 A2	24.00/3.5	24.00/3.0, 25.00/3.5	775	1752	787	5311	TL	220
775/65 R 29	CUT RESISTANT COMPOUND	E3	**	195 B	24.00/3.5	24.00/3.0, 25.00/3.5	775	1752	787	5311	TL	220
775/65 R 29	CUT RESISTANT COMPOUND	L3	*	206 A2	24.00/3.5	24.00/3.0, 25.00/3.5	775	1752	787	5311	TL	
775/65 R 29	CUT RESISTANT COMPOUND	L3	**	213 A2	24.00/3.5	24.00/3.0, 25.00/3.5	775	1752	787	5311	TL	
875/65 R 29 (35/65 R 29)	CUT RESISTANT COMPOUND	E3/L3	**/*	203 B/214 A2	27.00/3.50	27.00/3.0, 28.00/3.5	890	1860	816	5559	TL	279
875/65 R 29 (35/65 R 29)	CUT RESISTANT COMPOUND	E3	**	203 B	27.00/3.50	27.00/3.0, 28.00/3.5	890	1860	816	5559	TL	279
875/65 R 29 (35/65 R 29)	CUT RESISTANT COMPOUND	L3	*	214 A2	27.00/3.50	27.00/3.0, 28.00/3.5	890	1860	816	5559	TL	

Printed on 19/05/2024 06:57

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..