

## EARTHMAX SR 468 - Especificações técnicas



### Description

O EARTHMAX SR 468 é um pneu radial integralmente em aço, desenhado para os caminhões de mineração basculantes rígidos. Com compostos especiais, o design do piso é ideal para trabalhos em minas difíceis, rochosos e exigentes. Os blocos do piso com ranhuras em circunferência e os blocos entrelaçados garantem a dissipação efetiva do calor. Além disso, o design quadrado e resistente contribui para a ejeção de pedras soltas e a proteção do pneu contra danos. O EARTHMAX SR 468 foi desenvolvido com recurso à tecnologia de ponta da BKT, com vista a transportar cargas elevadas, oferecer durabilidade e garantir resistência a cortes e furos provocados por pedras.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Dumper Rígido

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	37.00 R 57
LI/SS	245 B

## Dimensions US Standard

Usa code	94069354
TMPH	497
Overall Width (inch)	40.6
Overall Diameter (inch)	134.8
Static Loaded Radius (inch)	59.8
Rolling Circumference (inch)	406.1
Rim Rec	27.00/6.0
Rim Alt	29.00/6.0
Star Rating	**
TRA Code	E4

## Load capacity (lbs)

mph / psi	80	83	87	91	94	98	102
30	96500	99000	102000	104500	107500	110000	113500

Printed on 18/05/2024 20:20

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..