

EARTHMAX SR 46 - Especificações técnicas



Description

Earthmax SR 46 para dumper rígidos é a resposta inovadora aos ambientes rochosos, abrasivos e hostis das minas. Este pneu foi especialmente projetado para o transporte de cargas pesadas e proporciona uma resistência excepcional a cortes e lacerações, bem como um ciclo de vida mais prolongado do produto. A carcaça e os cintos All Steel asseguram uma proteção extraordinária contra colisões, solicitações e furos para maximizar as horas de trabalho e aumentar a produtividade. Earthmax SR 46 é caracterizado por um desenho especial do piso do pneu, dotado de barras caracterizadas por blocos, com espaços ao longo da circunferência. Isto permite-lhes atingir ótimas prestações em curva com o mínimo dano na parte exterior do piso do pneu.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Dumper Rígido

| | |
|-----------|-------------------|
| Version | STANDARD COMPOUND |
| Type | TL |
| Tyre Size | 27.00 R 49 |
| LI/SS | 223 B |

Dimensions US Standard

| | |
|------------------------------|-----------|
| Usa code | 94050178 |
| TMPH | 404 |
| Overall Width (inch) | 29.4 |
| Overall Diameter (inch) | 105.8 |
| Static Loaded Radius (inch) | 48.2 |
| Rolling Circumference (inch) | 321.5 |
| Rim Rec | 19.50/4.0 |
| Rim Alt | - |
| Star Rating | ** |
| TRA Code | E4 |

Load capacity (lbs)

| mph / psi | 73 | 76 | 80 | 83 | 87 | 91 | 94 | 98 | 102 |
|-----------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 30 | 45400 | 48100 | 49400 | 50700 | 52000 | 55100 | 56800 | 58400 | 60000 |

Printed on 19/05/2024 14:30

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..