

AGRIMAX RT 600 - Specificații tehnice

Descriere

AGRIMAX RT 600 este anvelopa ideală pentru pajiști, recoltare și împrăștiere. Datorită suprafeței mari de contact, AGRIMAX RT 600 asigură o distribuție excelentă a presiunii pe sol, reducând deteriorarea pajiștilor și protejând solul. Datorită tehnologiei de muchie rotundă, talonului ranforsat și numărului crescut de caneluri, garantează o stabilitate și tracțiune deosebite.

UM

Standard internațional

Construcție

 RADIAL

Mașinării

Agricultură: Mașină de recoltare • Mașină de împrăștiat • Tractor



Versiune	STEEL BELTED
Tip	TL
Dimensiunea anvelopei	IF 1250/50 R 32 CFO
LI/SS	201 B

Dimensiuni Standard internațional

Lățimea secțiunii (mm)	1247
Overall Diameter (mm)	2063
Static Loaded Radius (mm)	897
Rolling Circumference (mm)	6136
SRI (mm)	975
Rim Rec	VA44/1.7 (multipiece)
ECE	E11-106R-006958

Load capacity (Kg)

km/h / bar	0.8	1.0	1.4	1.6	2.0	2.4	2.8	3.2	3.4	3.8
50	6525	7395	9280	10295	11455	12325	13485	14500	---	---
40	7115	8065	10120	11225	12490	13435	14700	15805	---	---
30	7615	8630	10830	12010	13365	14380	15735	16915	---	---
10 LT	9535	10805	13560	15040	16735	18005	19700	21180	---	---
10 HT	7615	8630	10830	12010	13365	14380	15735	16915	---	---
Upto 10 Cyc with front loader	---	11960	15320	16795	19485	21365	23380	25395	25800	26870

* For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Imprimat pe 5/19/2024 3:54 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..