

EARTHMAX SR 44 - Specificații tehnice



Descriere

EARTHMAX SR 44 este o anvelopă radială cu structură din oțel potrivită pentru o varietate de aplicații, inclusiv aplicații de minerit, transport și exploatare forestieră. Modelul E-4 al benzii de rulare asigură o tracțiune excelentă și un confort superior al operatorului. EARTHMAX SR 44 (E-4) este capabilă să optimizeze productivitatea indiferent de operațiune.

UM

US Standard

Construcție

 RADIAL

Mașinării

OTR: Camion On/Off

Versiune	STANDARD
Tip	TT
Dimensiunea anvelopei	12.00 R 24 (325/95 R 24)
LI/SS	158 B

Dimensiuni US Standard

Usa code	94034284
TMPH	96
Overall Width (inch)	12.2
Overall Diameter (inch)	49.2
Static Loaded Radius (inch)	22.6
Rolling Circumference (inch)	149.2
Rim Rec	8.50V
Rim Alt	9.00V
Star Rating	***
TRA Code	E4

Load capacity (lbs)

mph / psi	65	69	73	76	80	83	87	91	94	98	102
30	6800	6950	7400	7600	7850	8050	8250	8550	8800	9100	9350

Imprimat pe 5/19/2024 12:31 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..