

EARTHMAX SR 44 - Specificații tehnice



Descriere

EARTHMAX SR 44 este o anvelopă radială cu structură din oțel potrivită pentru o varietate de aplicații, inclusiv aplicații de minerit, transport și exploatare forestieră. Modelul E-4 al benzii de rulare asigură o tracțiune excelentă și un confort superior al operatorului. EARTHMAX SR 44 (E-4) este capabilă să optimizeze productivitatea indiferent de operațiune.

UM

Standard internațional

Construcție

 RADIAL

Mașinării

OTR: Camion On/Off

Versiune	STANDARD
Tip	TT
Dimensiunea anvelopei	325/95 R 24 (12.00 R 24)
LI/SS	158 B

Dimensiuni Standard internațional

TKPH	140
Overall Width (mm)	310
Overall Diameter (mm)	1250
Static Loaded Radius (mm)	575
Rolling Circumference (mm)	3790
Rim Rec	8.50V
Rim Alt	9.00V
Star Rating	***
TRA Code	E4

Load capacity (Kg)

km/h / bar	4.50	4.75	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00
50	3075	3150	3350	3450	3550	3650	3750	3875	4000	4125	4250

Imprimat pe 19.05.2024 05:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..