

FL 630 ULTRA - Specificații tehnice



Descriere

FL 630 ULTRA este potrivită pentru remorci, cisterne și mașini de împrăștiat agricole. Datorită talonului ranforsat și designului deosebit al benzii de rulare, este anvelopa ideală pentru utilizare multifuncțională pe orice tip de teren sau pe drum. FL 630 ULTRA asigură o compactare extraordinară de redusă a solului.

UM

US Standard

Construcție

 RADIAL

Mașinării

Agricultură: Mașină de împrăștiat • Cisternă • Remorcă

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	800/45 R 26.5
LI/SS	174 D/184 A8

Dimensiuni US Standard

Usa code	94054831
Lățimea secțiunii (inch)	32.6
Overall Diameter (inch)	54.8
Static Loaded Radius (inch)	24.3
Rolling Circumference (inch)	166.9
Rim Rec	AG 28.00
Rim Alt	AG 24.00
ECE	E11-106R-004074

Load capacity (lbs)

mph / psi	12	15	17	23	29	35	41	46	52	58
45	4310	4920	5520	6870	7800	9020	10230	11170	12250	13450
40	4730	5400	6060	7540	8580	9900	11230	12270	13450	14770
30	5730	6540	7340	9130	10370	11980	13590	14580	16280	17880
25	6350	7240	8130	10120	11510	13290	15080	16470	18050	19840
20	7140	8150	9150	11390	12940	14960	16960	18520	20300	22310
15	7470	8530	9580	11920	13550	15650	17750	19380	21250	23350
5	8510	9710	10900	13570	15420	17820	20220	22070	24190	26590

Imprimat pe 5/19/2024 6:14 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..