

AGRIMAX RT 600 - Технические спецификации

Description

Шины AGRIMAX RT 600 идеально подойдут для техники, используемой на пастбищах, а также для уборочной техники и разбрасывателей. Благодаря большой площади контакта с поверхностью земли шины AGRIMAX RT 600 обеспечивают отличное распределение давления, снижая повреждение пастбищ и защищая почву. Круглая плечевая зона, усиленный борт и увеличенное количество грунтозацепов гарантируют великолепную устойчивость и отличную тягу.

UM

US Standard

Construction

 RADIAL

Machinery

Сельское хозяйство: Комбайн • Разбрасыватель • Трактор-тягач



| | |
|-----------|-------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 750/70 R 26 |
| LI/SS | 172 A8/B |

Dimensions US Standard

| | |
|------------------------------|-----------------|
| Usa code | 94073146 |
| Section Width (inch) | 30.7 |
| Overall Diameter (inch) | 68.9 |
| Static Loaded Radius (inch) | 30.9 |
| Rolling Circumference (inch) | 207.4 |
| Rim Rec | DW 25 B |
| Rim Alt | DW 24 B |
| ECE | E11-106R-007934 |

Load capacity (lbs)

| mph / psi | 9 | 12 | 15 | 17 | 20 | 23 | 29 | 35 | 41 | 46 | 52 |
|-----------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 30 | 5970 | 6940 | 7930 | 8900 | 9780 | 10840 | 11950 | 12640 | 13890 | - | - |
| 25 | 5970 | 6940 | 7930 | 8900 | 9780 | 10840 | 11950 | 12640 | 13890 | - | - |
| 20 | 6400 | 7440 | 8490 | 9520 | 10570 | 11610 | 12800 | 13550 | 14880 | - | - |
| 5 LT | 8010 | 9310 | 10630 | 11930 | 13230 | 14540 | 16030 | 16950 | 18630 | - | - |
| 5 HT | 6400 | 7440 | 8490 | 9520 | 10570 | 11610 | 12800 | 13550 | 14880 | - | - |
| 5 Cyc | - | 11170 | 12730 | 14290 | 15850 | 17420 | 19200 | 20310 | 22320 | 22670 | 23610 |

Printed on 19.05.2024 3:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..