

ВК-LOADER 53 - Технические спецификации



Description

ВК-LOADER 53 - это шина с кордом из арамидного волокна, разработанная для погрузчиков, которые эксплуатируются в условиях промышленных предприятий. Уникальный рисунок протектора служит залогом невероятной устойчивости в поперечном направлении. А увеличенная высота этого рисунка гарантирует повышенный срок службы шины и ее стойкость к порезам и проколам. Шина ВК-LOADER 53 отличается превосходными характеристиками самоочистения, а также отличным сцеплением и тягой как на мокрых, так и на сухих покрытиях. Все эти качества делают ее оптимальным выбором для работы в сфере переработки отходов.

UM

International Standard

Construction

 RADIAL

Machinery

Производство: Погрузчик

Version	ARAMID BELTED
Type	TL
Tyre Size	365/70 R 18
LI/SS	146A2/142A4

Dimensions International Standard

Section Width (mm)	360
Overall Diameter (mm)	990
Static Loaded Radius (mm)	458
Rolling Circumference (mm)	3017
Rim Rec	11

Load capacity (Kg)

km/h / bar	1.5	2.0	2.5	3.0	3.5	4.0	4.5	5.0	5.5
20 TRANSPORT	930	1195	1405	1620	1855	2045	2255	2440	2650
10 LOADING	1050	1350	1590	1830	2100	2310	2550	2760	3000
STATIC	1670	2150	2530	2910	3340	3675	4055	4390	4770

Printed on 19.05.2024 16:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..